

CK850H Product Information



- **Throughput of 3tonnes per hour**
- **Bale weight in excess of 1tonne**
- **60tonnes compaction force**
- **Huge feed opening for bulky material**
- **Aggressive shearing system**

FEATURES	BENEFITS
Shear blade on top of press plate	Allows easy cutting of material
15kW motor	Reduced cycle time
Magic eye start-up	Operator can continuously feed machine, saving on down time
Automatic cut out when bale is full	The operator is informed of when the bale is ready to be tied
Tie off at any bale length	Can adjust the bale size to maximise the amount of material in a container
Simple operating controls	User friendly
Standard hopper	Enables easier feeding of machine, saving on labour time
Robust construction	Ensures long life of machine
IP55 rating	Allows machine to be installed indoors or outdoors
CE Marked	Ensures high safety standards

Standard CK850H supplied with:

- 15kW motor
- Hydraulic door ram
- Hand feed hopper
- Bale full indicator
- Jammed indicator
- Aggressive ram head

Optional extras:

- Oil heater
- Oil cooler
- Bobcat/ conveyor/ binlift hopper
- Trip bar on front of hopper
- Interlocked access door for any hopper

Optional extras:

- Bale eject counter cog
- Retention claws
- Door damper ram (recommended for retention claws)
- Vandal proof cover for control panel
- Hour counter
- Extra pressure setting
- Satellite control panel
- Bale discharged beacon/ jam beacon/ bale full beacon
- 1100L trunion binlift with 2m safety cage
- 1100L trunion binlift with 2.5m safety cage
- 6 wire tying